



# CD 180<sup>®</sup>

## DC SERVODRIVE



### CD 180<sup>®</sup>

**Stand alone, four quadrant bidirectional servodrives for controlling DC servomotors up to 30 Nm (4285,6 oz-in).**

**Typical applications are: Axis translation, packaging equipment, storage system lathes, welding robots and machining centers.**

#### STANDARD FEATURES

- ✓ Internal power supply and dumping circuit
- ✓ Ventilation on board when required
- ✓ Power block transistor bridge
- ✓ Power stage and optocoupled enable inputs
- ✓ Dynamic braking for blackout conditions
- ✓ Relay contacts for output signals
- ✓ Removable personality setting card
- ✓ Completely protected from:
  - over/under supply voltage
  - over temperature
  - external short circuit motor polarity
  - max dynamic braking cycle
  - broken or inverted tachometer

#### OPTIONS

- ✓ Synoptic: remote check status panel
- ✓ Boosted dumping (with external resistors)

#### SPECIFICATIONS

- ✓ Supply voltage range: 110÷170 VAC (50/60 Hz±10%)
- ✓ Output voltage: 1.35x VAC supply
- ✓ Operating frequency: 5 KHz
- ✓ Operating temperature: 0÷40°C (32÷104°F)
- ✓ Humidity (without condensation): 10÷95%
- ✓ Enable signals: +10÷30 VDC (optocoupled)
- ✓ Analog input reference (differential): ±10 Vdc (24 KOhm)
- ✓ Peak current limitation with speed function



#### DESCRIPTION

The **CD 180<sup>®</sup>** Servodrive is a traditional transistor converter for DC servomotors. Easy-to-use and extremely trustworthy, it is an ideal solution for retro fitting applications. Every servodrive comes complete with its own power supply, regenerative circuit and internal fan cooling.

Because of the autogeneration of the internal auxiliary voltages, a three phase transformer with only one secondary is enough for their supply.

Auto transformers are also allowed. Usually the **CD 180<sup>®</sup>** Servodrive doesn't require external choke before the motor, thanks to its 5 KHz special frequency "cross-modulation".

MODEL	CD 180	CD 180	CD 180	CD 180	CD 180	CD 180	CD 180
SIZE (A)	8/16	12/24	15/30	25/50	30/75	50/100	50/150
Rated Current (A <sub>dc</sub> )	8	12	15	25	30	50	50
Peak Current (A <sub>dc</sub> ) x 5 sec.	16	24	30	50	75	100	150
F2: Supply Line Fuses (T-type = time-lag)	12 A 250 V		16 A 250 V	25 A 250 V	35 A 250 V	50 A 250 V	80 A 250 V
Supply (V <sub>ac</sub> ) (3PH-50/60 Hz)	110÷170 Vac						

